

TECHNICAL SPECIFICATIONS

T9000 PTAC wireless control node.

GENERAL

Enclosure:

None — Open stacked 2-PCB
4.75”L x 3.20”W x 1.50”H

Mounting:

7/16" tall stainless steel unthreaded through-hole
standoff — use #6 machine or sheet metal screws.

ELECTRICAL

Operating Power:

24vac @ .6VA quiescent circuit board
Plus maximum of 12VA per triac load*

(*Use a U.L. Recognized Class-2 power transformer
rated for required loading conditions.)

Input/Output:

6 - pilot duty triac outputs @ 0.5A max each
2 - dry contact closure inputs w/5vdc pull-up

ESD Withstand Voltage for No Hard Failures:

2.0 kV

Standards:

FCC Part 15

LEDs:

6 - Control Output Status
2 - Input Status
1 - Call for HEAT/COOL
1 - HEAT Status
1 - COOL Status
1 - FAN Status
1 - Service Pin

ENVIRONMENTAL

Temperature Range:

Operating: 0° to +70°C
Storage: -40° to +85°C

Humidity Range:

10% to 95% RH, non-condensing at 70°C

COMMUNICATION

Physical Layer:

916.5 MHz Amplitude Shift Keyed

Packet Communications Protocol:

ANSI 709.1-1999

Communication Rate:

9600 bps

Options:

Pager-based direct load control
Local operating network capable

FOR MORE INFORMATION CONTACT

E N E R N E T
Corporation

307 Dewittshire Road, Syracuse, New York 13214

Phone: (315) 449-0839

Fax: (315) 449-3056

Email: corpsales@enernetcorp.com

Web: <http://www.enernetcorp.com>
